

| | | EN | VIRON | MEN | TAL | STAT | EMENT | 1 |
|---------------------------------------|-----------|----------------------|----------|-----------------|---------------|-----------|------------------|----------------------------|
| GENERATING S | SET – A | V1614 | 13 | | | | | |
| Model | R066C3 IV | | | | Serial number | | | 16014315 |
| Manufacturer | SDM | SDMO | | | | | | |
| Year of manufactu | re 2016 | | | | ı | | | |
| | | | | | | | | |
| ENGINE | | | | | | | | |
| Manufacturer | Mits | Mitsubishi | | Model | | | HFS85 | Displacement (I) 4.48 |
| ower 60 | | | Seria | | | 045L30608 | | |
| Engine complies w | | EU Stage | II 🗵 |] EU S | tage II | IA | EU S | tage IV 🔲 EPA |
| ☐ Ga | | nleaded petrol as | | Fuel consumptio | | 15 % | | |
| Emissions accordi | | : 0.62 + NOx : 4 | 1.16 | | | | | |
| to ISO8178 (g/kWh | PM | : 0.23 | | | | | | |
| DILS AND LUB | | | I | | | | | |
| | Brand | | Тур | | | | Volume | Time between 2 changes (1) |
| Engine | Genpart | Genpart Lub | | Mineral 🛛 | | | 12 liters | Every 750 hours |
| Compressor | | | | | Synth | etic | | |
| Coolant | Gencool | lene | | | 17 liters | | | |
| NOISE EMISSION (ACCORDING 2000/14/CE) | | | r manual | PAINTINGS | | | | BATTERY |
| Sound power level | | | | Wa | Water Y | | es 🖂 No | Number: 1 |
| Sound pressure le | | @ 7 m in dB(A) : 66 | | | | | es 🖂 No | Type: 12V |
| Sound pressure le | vei | | | Solvents Ye | | | \$5 ⊠ NO | 1 1 7. |
| IRE | | uв(л) . | | | | | | electrolytic |
| | | | | | | | | |
| The machine is fitted with sprinkler | | | | | ☐ Yes ⊠No | | | |
| OTHER EQUIPM | MENT | | | | | | | |
| Includes brake pag | ds. mercu | rv. cadm | ium or a | sbesto |)S | ⊠N | 0 | |
| Includes a frame, h | | | | | | X | | |
| Includes electric o | | | pomoi | 34510 | | X | | |
| | | | | | | | <u> </u> | |
| | | | | | | Issu | | est : 08/03/16 |
| | | | | | | FP | OYFR | |
| | | | | | | | OYER umentati | on and Standards Office |